# Product datasheet

Specifications



## High power contactor, TeSys Giga, 3 pole (3NO), AC-3 <=440V 265A, standard version, 48…130V wide band AC/DC coil

LC1G265EHEN

## Main

| | |
|---|---|
| **Range** | TeSys |
| **Range of product** | TeSys Giga |
| **Product or component type** | Contactor |
| **Device short name** | LC1G |
| **Contactor application** | Power switching<br>Motor control |
| **Utilisation category** | AC-1<br>AC-3<br>AC-3e<br>AC-4<br>AC-5a<br>AC-5b<br>AC-6a<br>AC-6b<br>AC-8b<br>AC-8a<br>DC-1<br>DC-3<br>DC-5 |
| **Poles description** | 3P |
| **[Ue] rated operational voltage** | <= 1000 V AC 50/60 Hz<br><= 460 V DC |
| **[Ie] rated operational current** | 385 A (at <40 °C) at <= 1000 V AC-1<br>265 A (at <60 °C) at <= 440 V AC-3 |
| **[Uc] control circuit voltage** | 48...130 V AC 50/60 Hz<br>48...130 V DC |
| **Control circuit voltage limits** | Operational: 0.8 Uc Min...1.1 Uc Max (at <60 °C)<br>Drop-out: 0.1 Uc Max...0.45 Uc Min (at <60 °C) |

## Complementary

| | |
|---|---|
| **[Uimp] rated impulse withstand voltage** | 8 kV |
| **Overvoltage category** | III |
| **[Ith] conventional free air thermal current** | 385 A (at 40 °C) |
| **Rated breaking capacity** | 2380 A at 440 V |
| **[Icw] rated short-time withstand current** | 2.2 kA - 10 s<br>1.23 kA - 30 s<br>0.95 kA - 1 min<br>0.62 kA - 3 min<br>0.48 kA - 10 min |
| **Associated fuse rating** | 315 A aM at <= 440 V for motor<br>250 A aM at <= 690 V for motor<br>400 A gG at <= 690 V |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|---|---|
| **Average impedance** | 0.000144 Ohm |
| **[Ui] rated insulation voltage** | 1000 V |
| **Power dissipation per pole** | 20 W AC-1 - Ith 385 A<br>11 W AC-3 - Ith 265 A |
| **Compatibility code** | LC1G |
| **Pole contact composition** | 3 NO |
| **Auxiliary contact composition** | 1 NO + 1 NC |
| **Motor power kW** | 75 kW at 230 V AC 50/60 Hz (AC-3e)<br>132 kW at 400 V AC 50/60 Hz (AC-3e)<br>132 kW at 415 V AC 50/60 Hz (AC-3e)<br>160 kW at 440 V AC 50/60 Hz (AC-3e)<br>160 kW at 500 V AC 50/60 Hz (AC-3e)<br>200 kW at 690 V AC 50/60 Hz (AC-3e)<br>160 kW at 1000 V AC 50/60 Hz (AC-3e)<br>75 kW at 230 V AC 50/60 Hz (AC-3)<br>132 kW at 400 V AC 50/60 Hz (AC-3)<br>132 kW at 415 V AC 50/60 Hz (AC-3)<br>160 kW at 440 V AC 50/60 Hz (AC-3)<br>160 kW at 500 V AC 50/60 Hz (AC-3)<br>200 kW at 690 V AC 50/60 Hz (AC-3)<br>160 kW at 1000 V AC 50/60 Hz (AC-3)<br>75 kW at 230 V AC 50/60 Hz (AC-4)<br>132 kW at 400 V AC 50/60 Hz (AC-4)<br>132 kW at 415 V AC 50/60 Hz (AC-4)<br>150 kW at 440 V AC 50/60 Hz (AC-4)<br>160 kW at 500 V AC 50/60 Hz (AC-4)<br>160 kW at 690 V AC 50/60 Hz (AC-4)<br>160 kW at 1000 V AC 50/60 Hz (AC-4) |
| **Motor power hp** | 75 hp at 200/208 V 60 Hz<br>100 hp at 230/240 V 60 Hz<br>200 hp at 460/480 V 60 Hz<br>200 hp at 575/600 V 60 Hz |
| **Irms rated making capacity** | 3320 A at 440 V |
| **Coil technology** | Built-in bidirectional peak limiting |
| **Safety reliability level** | B10d = 400000 cycles contactor with nominal load conforming to EN/ISO 13849-1<br>B10d = 3000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1 |
| **Mechanical durability** | 8 Mcycles |
| **inrush power in VA (50/60 Hz, AC)** | 780 VA |
| **inrush power in W (DC)** | 695 W |
| **hold-in power consumption in VA (50/60 Hz, AC)** | 17.6 VA |
| **hold-in power consumption in W (DC)** | 7.8 W |
| **Operating time** | 40...70 ms closing<br>15...50 ms opening |
| **Maximum operating rate** | 600 cyc/h AC-3<br>600 cyc/h AC-3e<br>300 cyc/h AC-1<br>150 cyc/h AC-4 |
| **Connections - terminals** | Power circuit: bar 2 - busbar cross section: 32 x 10 mm<br>Power circuit: lugs-ring terminals 1 185 mm²<br>Power circuit: bolted connection<br>Control circuit: push-in 1 0.2…2.5 mm² - cable stiffness: solid stranded without cable end<br>Control circuit: push-in 1 0.25…2.5 mm² - cable stiffness: flexible with cable end<br>Control circuit: push-in 2 0.5…1.0 mm² with cable end<br>Control circuit: push-in 0.75…2.5 mm² - cable stiffness: solid stranded without cable end<br>Control circuit: push-in 0.75…2.5 mm² - cable stiffness: flexible with cable end |
| **Connection pitch** | 45 mm |

| | |
|---|---|
| **Mounting support** | Plate |
| **Standards** | EN/IEC 60947-4-1<br>EN/IEC 60947-5-1<br>UL 60947-4-1<br>CSA C22.2 No 60947-4-1<br>JIS C8201-4-1<br>JIS C8201-5-1<br>IEC 60335-1:Clause 30.2<br>IEC 60335-2-40:Annex JJ<br>UL 60335-1<br>UL 60335-2-40:Annex JJ |
| **Product certifications** | CB Scheme<br>CCC<br>cULus<br>EAC<br>CE<br>UKCA<br>EU-RO-MR by DNV-GL |
| **Tightening torque** | 35 N.m |
| **Height** | 225 mm |
| **Width** | 140 mm |
| **Depth** | 226 mm |
| **Net weight** | 7.5 kg |

## Environment

| | |
|---|---|
| **IP degree of protection** | IP2X front face with shrouds conforming to IEC 60529<br>IP2X front face with shrouds conforming to VDE 0106 |
| **Ambient air temperature for operation** | -25…60 °C |
| **Ambient air temperature for storage** | -60…80 °C |
| **Mechanical robustness** | Vibrations 5…300 Hz 2 gn contactor open<br>Vibrations 5…300 Hz 4 gn contactor closed<br>Shocks 10 gn 11 ms contactor open<br>Shocks 15 gn 11 ms contactor closed |
| **Colour** | Dark grey |
| **Protective treatment** | TH |
| **Permissible ambient air temperature around the device** | -40…70 °C at Uc |

## Packing Units

| | |
|---|---|
| **Unit Type of Package 1** | PCE |
| **Number of Units in Package 1** | 1 |
| **Package 1 Height** | 31.000 cm |
| **Package 1 Width** | 22.500 cm |
| **Package 1 Length** | 31.500 cm |
| **Package 1 Weight** | 7.478 kg |
| **Unit Type of Package 2** | S06 |
| **Number of Units in Package 2** | 4 |
| **Package 2 Height** | 105.000 cm |
| **Package 2 Width** | 60.000 cm |
| **Package 2 Length** | 80.000 cm |
| **Package 2 Weight** | 39.912 kg |

## Sustainability

**Green Premium$^{TM}$ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-$CO_2$ products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency



RoHS/REACh

## Well-being performance

| | |
|---|---|
| Mercury Free | |
| Rohs Exemption Information | Yes |

## Certifications & Standards

| | |
|---|---|
| **Reach Regulation** | REACh Declaration |
| **Eu Rohs Directive** | Compliant with Exemptions |
| **China Rohs Regulation** | China RoHS declaration |
| **Environmental Disclosure** | Product Environmental Profile |
| **Circularity Profile** | End of Life Information |

## Installation

### Installation Videos

TeSys Giga - How to install the auxiliary contact block
TeSys Giga - How to install and remove remote wear diagnosis module
TeSys Giga - How to install mechanical interlock kit
TeSys Giga - How to install cable memory kit
TeSys Giga - How to directly mount LR9G overload relay
TeSys Giga - How to replace control module
TeSys Giga - How to replace switching modules
TeSys Giga - How to assemble reverser solution
TeSys Giga - How to assemble change-over solution