# Product datasheet

Specifications



## Mureva Styl - double two-way switch - surface mounting - grey

MUR35022

## Main

| | |
|---|---|
| **Range** | Mureva Styl |
| **Range of product** | Mureva Styl |
| **Product or component type** | Switch |
| **Colour tint** | Anthracite (RAL 7016) |

## Complementary

| | |
|---|---|
| **Device presentation** | Complete product |
| **Device mounting** | Surface |
| **Switch function** | 1-pole 2-way |
| **Fixing mode** | By screws |
| **Rated current** | 10 AX |
| **Technology type** | Electromechanical |
| **Load type** | Load for energy saving lamps with ballast: 100 W |
| **[Ue] rated operational voltage** | 250 V AC |
| **Condition of use** | Indoor/outdoor |
| **Number of rocker** | 2 |
| **Material** | SEBS<br>Brass<br>ABS (acrylonitrile butadiene-styrene) |
| **Actuator** | Rocker |
| **Wire stripping length** | 13 mm |
| **Cable entry** | Easy valve access diameter: 6…20 mm |
| **Clamping connection capacity** | 1.5...2.5 mm² for rigid cable(s)<br>1.5...2.5 mm² for stranded cable(s)<br>1.5...2.5 mm² for flexible cable(s) |
| **Connections - terminals** | Screwless terminals |
| **Width** | 76 mm |
| **Height** | 76 mm |
| **Depth** | 64 mm |
| **Projecting depth** | 64 mm |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|---|---|
| **Chemical and detergent products resistance** | Resistant to alcohol (70 %)<br>Resistant to alcohol (96 %)<br>Resistant to A-Lactic Acid<br>Resistant to diluted quaternary ammonium<br>Resistant to diluted bleach<br>Resistant to diluted ammonia<br>Resistant to soapy water<br>Resistant to crystal cleaner<br>Resistant to hydrogen peroxide 10 volumes<br>Resistant to hexane |

## Environment

| | |
|---|---|
| **Quality labels** | CE<br>NF<br>AENOR<br>EAC |
| **IP degree of protection** | IP55 |
| **IK degree of protection** | IK08 |
| **Flame retardance** | Self-extinguishing 650 °C conforming to IEC 60695-2-1 |
| **Standards** | EN 60669-1 |
| **ambient air temperature for operation** | -5…40 °C |
| **Ambient air temperature for storage** | -25…55 °C |

## Packing Units

| | |
|---|---|
| **Unit Type of Package 1** | PCE |
| **Number of Units in Package 1** | 1 |
| **Package 1 Height** | 7.600 cm |
| **Package 1 Width** | 6.500 cm |
| **Package 1 Length** | 7.600 cm |
| **Package 1 Weight** | 128.000 g |
| **Unit Type of Package 2** | BB1 |
| **Number of Units in Package 2** | 10 |
| **Package 2 Height** | 8.000 cm |
| **Package 2 Width** | 16.000 cm |
| **Package 2 Length** | 39.500 cm |
| **Package 2 Weight** | 1.370 kg |
| **Unit Type of Package 3** | S04 |
| **Number of Units in Package 3** | 60 |
| **Package 3 Height** | 30.000 cm |
| **Package 3 Width** | 40.000 cm |
| **Package 3 Length** | 60.000 cm |
| **Package 3 Weight** | 8.962 kg |

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

### Environmental footprint

| | |
|---|---|
| Carbon footprint (kg.eq.CO2 per CR, Total Life cycle) | 1 |
| Environmental Disclosure | Product Environmental Profile |

## Use Better

### Materials and Substances

| | |
|---|---|
| Packaging made with recycled cardboard | Yes |
| Packaging without single use plastic | No |
| EU RoHS Directive | Compliant |
| SCIP Number | 66b36458-2ef6-42ba-b429-8005a46f0a37 |
| REACh Regulation | REACh Declaration |

## Use Again

### Repack and remanufacture

| | |
|---|---|
| Circularity Profile | No need of specific recycling operations |
| Take-back | No |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

Image of product / Alternate images

**Alternative**












K50
Schneider Electric
K50

